

# RKI GX-3R GAS DETECTOR

## DESCRIPTION

The GX-3R is the worlds smallest 4 gas monitor weighing only 3.52 ounces and can comfortably be clipped within a worker's breathing zone (2.2" W x 2.55" H x 1.02" D). It simultaneously monitors and displays LEL combustibles, O<sub>2</sub>, CO (Hydrogen compensated CO also available), and H<sub>2</sub>S.

## FEATURES

- Smallest & lightest 4 gas monitor
- 2.2" W x 2.55" H x 1.02" D, 3.52 ounces
- Simultaneous detection of 4 gases
- LEL, O<sub>2</sub>, H<sub>2</sub>S & CO
- H<sub>2</sub> Compensated CO sensor available
- Simple 2-button operation
- Non-Compliance Indicator
- Alarms: audible, visual, & vibration
- 3 user adjustable alarm levels
- 25 hours of operation (Lithium-ion battery)
- Water and dust resistant design, IP66/68
- 3 Year warranty
- New Product of the Year 2020



Gas Detected	All Combustible gases (Methane as standard)	Oxygen (O <sub>2</sub> )	Hydrogen Sulphide (H <sub>2</sub> S)	Carbon Monoxide (CO)
Detection Principle	Catalytic Combustion	Electrochemical cell	Dual Electrochemical cell	
Detection Range (Increments)	0 – 100% LEL (1% LEL)	0 – 25.0% Vol (0.1% Vol)	0 – 100 ppm (0.5 ppm)	0 – 500 ppm (1 ppm)
Sampling Method	Diffusion sampling, hand aspirator or motorised pump optional			
Display	Digital LCD displays with 7 segment plus 14 segment plus icon			
Present Alarms (User Adjustable)	1st alarm      5% LEL 2nd alarm      10% LEL Over alarm     100% LEL	Low alarm      19.5% High alarm     23.5% Over alarm     40.0%	1st alarm      10 ppm 2nd alarm      15 ppm TWA alarm      10 ppm STEL alarm     15 ppm Over alarm     200 ppm	1st alarm      30 ppm 2nd alarm      60 ppm TWA alarm      30 ppm STEL alarm     60 ppm Over alarm     2000 ppm
Types of Alarms	Gas Alarm:                      2 Increasing alarms, STEL, TWA, overscale alarm. O2 decreasing/increasing. Trouble Alarm:                Sensor disconnection, low battery, circuit error, calibration range error			
Display of Alarms	Gas Alarm:                      Flashing LEDs, continuous buzzer (100 db @ 30 cm), flashing gas value, vibration Trouble Alarm:                Flashing LEDs, intermittent buzzer (95 db @ 30 cm), display of error message			
Operating Temp & Humidity	-40°C to +60°C, 0 to 95% RH, non-condensing (splash resistant)			
Response Time	Within 30 seconds (T90)			
Continuous Operation	25 hours after a full 3 hour charge			
Power Source	Lithium-ion battery			
Safety Design/Approvals	Ex da ia IIC T4 Ga or EX ia IIC T4 Ga and EX da ia I MA or EX ia I Ma (IECEx) / I M1Ex da ia I Ma//II 1G Ex da ia I ICT4 Ga (ATEX)			
Dimension & Weight	Approx 55mm (H) x 64mm (W) x 26mm (D), approx 100g			
Case Material	Explosion proof, dust and water resistant to IP-68 (2m,1h) approval. Drop height 7m			
Controls	Two buttons: POWER / MODE, AIR			
Datalogging	Logs user ID, station ID, Calibration & Bump Test history, Alarm Events & Alarm Trends			
Standard Accessories	Alligator clip Charger Calibration cup			
Optional Accessories	Padded carrying case for GX-3R and accessories RP-3R Attachable sampling Pump with tapered rubber nipple, 3m hose and probe (up to 12m hose available) USB to IrDA downloading cable for datalogger SDM-3R calibration station Calibration Cup			
Warranty	Three years material and workmanship			

